

UNITY₂₀

TECHNICAL DATASHEET

UNITY₂₀



DE/EN

KOSTAD

www.kostad.at | www.kostad.ch

Product information | User interface | Configuration | General features | Certification and standards

Bezeichnung**Kostad UNITY 20 Wallbox**

DE

Type der Ladung	DC Schnellladung
Ausgänge	CCS, CHAdeMo (optional)
AC-Eingangsleistung	C, CJ: 32 A, 22 kVA @ 50Hz @ 400V / C, CJ: 40 A, 28 kVA @ 50Hz @ 400V
Eingangsspannungsbereich	400 VAC +/- 10% (47-63HZ) -CE Version
DC-Ausgangsleistung	22kW ; 30kW (optional)
DC-Ausgangsspannung	200-1000 VDC
Anzahl der geladenen Fahrzeuge	1
Kabellänge	3,5m (vom Gehäuse-Ausgang) optional: 4,5 / 5,5 / 6,5 / 7,5 m (+/- 10%)
Max. Strom der CCS Ladeleitung	80A
Max. Strom der CHAdeMO Ladeleitung	80A
EMV	Class B (residential) conducted and Class B (residential) radiated emissions according to EN 61000-6-3:2007; EN61581-21-2
Netzanschluss	3P + PE
Schutzart	Überstrom, Überspannung, Unterspannung, Isolationsüberwachung, integrierter Überspannungsschutz
Überspannungskategorie	Type II
Powerfactor (Volllast)	> 0.97...0.99
THDI	< 5 %
Effizienz	> 95,5 % (peak)
Standby-Leistung	70 W
Kurzschlussspannung	< 50V / Netzabhängig
Vorlade-Strom	< 1 A
Engergiemessung	Optional: MID-Messung für DC- Ausgänge Optional: Eichrechtskonforme Ausführung (Q4 2023)
Netzwerkanbindung	GSM / 4G / LTE

Benutzeroberfläche

Konnektivität	Internet Zugriff via 4G/3G/Ethernet (RJ45)
Benutzerauthentifizierung	RFID
Benutzeroberfläche	7" LCD; 7" LCD direct sunlight (optional)
Kommunikationsprotokolle	OCPP 1.6/ OCPP 2.0 JSON
RFID-Leser	ISO 14443 A + B to part 4 and ISO/IEC 15693, Mifare, NFC
Not-Aus-Taste	Ja

Konfiguration

Softwareupdate	Over-the-air updates via Kostad
Steuerung & Konfiguration	Kostad HMI am Display Konfigurator
Sprachen	Deutsch, Englisch sowie mehr als 15 weitere Sprachen verfügbar

Allgemeine Eigenschaften

IP und IK Klassen	IP54 and IK10 (Gehäuse) / IK8 (Touchscreen)
Gehäusetyp	Edelstahl
Betriebshöhe	Bis 2000m
Betriebstemperatur	-30 °C bis + 50 °C
Temperatur-Derating	Umgebungstemperatur bis 50 °C: 100% Ausgangsleistung Umgebungstemperatur über 50 °C: Leistungsreduzierung (Derating)
Lagertemperatur	-40 °C bis + 70 °C
Feuchtigkeit	20-95 % Rh nicht kondensierend
Montageart	Wandbefestigung; Standfuß (optional)
Abmessungen (HxBxT)	650 x 500 x 230mm
Gewicht	65kg

Zertifizierung und Standards

Ladesystem	ICE 61851-1 ed 3, ID 61851-21-2, IEC 61851-23 ed 1, IEC 61851-24 ed 1, IEC 62196-2, IEC 62196-3, IEC 61000
Kommunikation zum EV	Din 70121, CHAdeMO 1.2
Kommunikation zum Backend	OCPP 1.6/2.0 JSON ready

Name	Kostad UNITY 20 Wallbox	EN
Charging type	DC fast charging	
Outputs	CCS, CHAdeMO	
AC power input	C, CJ: 32 A, 22 kVA @ 50Hz @ 400V; C, CJ: 40A, 28kVA @ 50Hz 400V	
Input voltage range	400 VAC +/- 10% (47-63 Hz) CE version	
DC power output	22kW ; 30kW (option)	
DC output voltage	200-1000 VDC	
Number of vehicles charged	1	
Cable length	3,5 m (from housing outlet) Optional: 4,5 / 5,5 / 6,5 / 7,5 m (+/- 10%)	
Max. current of CCS charging cable	80A	
Max. current of CHAdeMO charging cable	80A	
EMC	Class B (residential) conducted and Class B (residential) radiated emissions according to EN 61000-6-3:2007; EN61581-21-2	
Mains connection	3P + PE	
Protection class	Overcurrent, overvoltage, undervoltage, insulation monitoring, integrated surge protection	
Overvoltage category	Type II	
Power factor (full load)	> 0.97...0.99	
THDI	< 5 %	
Efficiency	>95.5% (peak)	
Standby output	70 W	
Impedance voltage	<50 V / network-dependent	
Precharge current	< 1 A	
Power measurement	Optional: MID measurement for DC outputs Optional: Eichrecht compliant solution for DC outputs (Q4 2023)	
Network connection	GSM / 4G / LTE	
User interface		
Connectivity	Internet access via 4G/3G/Ethernet (RJ45)	
User authentication	RFID	
User interface	7" LCD; 7" LCD direct sunlight (option)	
Communication protocols	OCPP 1.6/ OCPP 2.0 JSON	
RFID reader	ISO 14443 A + B to part 4 and ISO/IEC 15693, Mifare, NFC	
Emergency off button	Yes	
Configuration		
Softwareupdate	Over-the-air updates via Kostad	
Control & configuration	Kostad HMI on display configurator	
Languages	German, English and more than 15 other languages available	
General features		
IP and IK ratings	IP54 and IK10 (housing) / IK8 (touchscreen)	
Housing type	Stainless steel	
Operating altitude	Up to 2000 m	
Operating temperature	-30 °C bis + 50 °C	
Temperature derating	Ambient temperature up to 50°C: 100% power output Ambient temperature above 50°C: Power reduction (Derating)	
Storage temperature	-40 °C bis + 70 °C	
Humidity	20-95% Rh, non-condensing	
Installation type	Wall-mounted; Stand (option)	
Dimensions (HxWxD)	650 x 500 x 230mm	
Weight	65kg	
Certification and standards		
Charging system	IEC 61851-1 ed 3, ID 61851-21-2, IEC 61851-23 ed 1, IEC 61851-24 ed 1, IEC 62196-2, IEC 62196-3, IEC 61000	
Communication with EV	DIN 70121, CHAdeMO 1.2	
Communication with backend	OCPP 1.6/2.0 JSON ready	